G11MA7-P04QJ00-0070

odu medi snap®

receptacle with break away and push pull locking for front panel mounting

size: 1, IP50, keying: a, number of contacts: 4, pcb, contact type: sockets, Signal

Basic information

Part number	G11MA7-P04QJ00-0070
Category	connector
Type of connector	receptacle
Assembly situation	front panel mounting
Size	1

Contact insert description

Special features	iec 60601 1 1 mopp & 2 moop
Transmission type	Signal
Number of contacts	4
Contact type	sockets
Contact diameter	0.9 mm
Termination type	pcb
Termination diameter	0.7 mm

Technical information

Nominal current single contact	7.5 A	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Max. current insert	7.5	VDE 0298-4:2003
Test voltage	1.3 kV AC	EIA-364-20F:2019-02
Max. creepage distance (contact to contact)	1.2 mm (Contact to housing)	
Max. creepage distance (contact to housing)	IEC 60601-1: 1MOPP. 2MOOP*	
Max. clearance distance (contact to contact)	1.2 mm (Contact to contact)	
Max. clearance distance (contact to housing)	IEC 60601-1: 1MOPP. 2MOOP*	

Mechanical and environmental data

Locking principle	break_away , push_pull
Keying	a
Mating cycles	5000
IP class	IP50
Max. operating temperature	120 °C
Min. operating temperature	50 °C

Material and surface treatments

Material	psu_gray
Insulator material	peek
Contact material	cu_alloy_with_gold_finish
Color option (Front or back nut)	gray

Insulator materials MEDI-SNAP®

psu_peek_o_a



CODING: 40 °



POSITIONS: 4 Positions



PCB-LAYOUT:



Borehole 0.8 mm

PANEL CUT OUT:



f_graphics_pcb_layout_sockets

Further technical information and downloads

3D-File (STP File)