


**G52LFC-P04QP00-0000**  
**series\_l, type\_g5**



**General information**

<b>Part number</b>	G52LFC-P04QP00-0000
<b>Termination</b>	pcb
<b>Size</b>	2
<b>Locking principle</b>	break , push
<b>Coding</b>	f_key



Illustrations may differ from original product.  
 Dimensions, unless otherwise specified, in mm.

**POSITIONS:** 4 Positions

**PANEL CUT OUT:**

**DIMENSIONS:**

The pin layout corresponds to the view on the termination area

**Contact insert description**

<b>Number of contacts</b>	4
<b>Contact type</b>	sockets
<b>Contact diameter</b>	13mm
<b>Insulator material</b>	peek
<b>Termination</b>	pcb
<b>Termination diameter</b>	07mm
<b>Data transmission</b>	ethernet_100

reverse\_gender\_on\_request

**Technical information**

<b>Max. creepage and air clearance distance</b>	18_mm	16_mm
<b>Nominal current single contact</b>	12_a	iec_60512_5_2
<b>Nominal current insert</b>	12 A	vde_0298_4
<b>Test voltage</b>	195_kv_ac	sae_13441

safety\_text

**Mechanical and environmental data**

<b>Degree of protection*</b>	ip50
<b>Operating temperature</b>	40_120_c
<b>Mating cycles</b>	5000

mated\_unmated

### Material and surface treatments

<b>Housing</b>	m_chrome
<b>Contact</b>	cu_alloy_gold

safety\_text\_2  
data\_text  
ul\_text  
illustrative\_text