
G82YAR-P26UC00-000L ODU AMC[®], Receptacle for rear panel mounting



General information

Part number	G82YAR-P26UC00-000L	Illustrations may differ from original product. Dimensions, unless otherwise specified, in mm.
Termination	PCB	
Size	2	
Locking principle	Break-Away , Push-Pull	
Coding	A (light brown)	
Cable Diameter	5 – 10.0 mm	



The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	26	
Contact type	Sockets	
Contact diameter	0.5 mm	
Insulator material	PEEK	
Termination	PCB	
Termination diameter	0.5 mm	
Reverse gender on request		
Technical information		
Nominal current single contact	5 A	IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003)
Test voltage	0.9 kV AC	EIA-364-20F:2019-02

All shown connectors are rated to a safety extra low voltage (SELV) of less than 50 V AC / 75 V DC, according to IEC 61140:2016 (VDE 0140-1:2016) Protection against electric shock - Common aspects for installation and equipment. In case other standards rule a specific use of the connector, the application specific safety criteria shall be considered first. In this context, lower voltage ratings may be valid. Warning: Danger to life for operating voltages above 50 V AC / 120 V DC!

Mechanical and environmental data

Degree of protection*	IP6K8 / IP6K9K
Operating temperature	-51 °C – 125 °C
Mating cycles	5000

*mated condition

Material and surface treatments

Housing	Cu-alloy with ruthenium finish
Contact	Cu-alloy with gold finish

All shown connectors are defined without breaking capacity (COC) according to IEC 61984:2008 (VDE 0627:2009). ODU MEDI-SNAP® and MINI-SNAP® are UL-approved (E110586).

ODU reserves the right to make changes based on the current state of knowledge without prior notice without being obliged to

provide replacement deliveries or refinements of older designs.