

General information

| | |
|-------------------|---------------------|
| Part number | G83YAR-P26WFG0-000L |
| Termination | solder |
| Size | 3 |
| Locking principle | break , push |
| Coding | a_key_amc |
| Cable Diameter | cable_amc_3 |



Illustrations may differ from original product. Dimensions, unless otherwise specified, in mm.

CODING:A

POSITIONS: 26 positions

PANEL CUT OUT:

DIMENSIONS:

The pin layout corresponds to the view on the termination area

Contact insert description

| | |
|----------------------|---------|
| Number of contacts | 26 |
| Contact type | sockets |
| Contact diameter | 07mm |
| Insulator material | peek |
| Wire cross section | 22_awg |
| Termination | solder |
| Termination diameter | 085mm |

reverse_gender_on_request

Technical information

| | | |
|--------------------------------|---------|---------------|
| Nominal current single contact | 07_a | iec_60512_5_2 |
| Test voltage | 1_kv_ac | eia_364_20f |

safety_text

Mechanical and environmental data

| | |
|-----------------------|--------------|
| Degree of protection* | ipsk8_ip6k9k |
| Operating temperature | 51_125_c |
| Mating cycles | 5000 |

mated

Material and surface treatments

| | |
|----------------|---------------|
| Housing | ruthenium |
| Contact | cu_alloy_gold |

safety_text_2
ul_text
illustrative_text