

General information

Part number	GKOWBM-P09UM00-000L
Termination	pcb
Size	0
Locking principle	break
Coding	b_key_amc
Cable Diameter	cable_amchd_0



Illustrations may differ from original product. Dimensions, unless otherwise specified, in mm.

<p><b>CODING:</b>B</p>	<p><b>POSITIONS:</b> 9 positions</p>	<p><b>PANEL CUT OUT:</b></p>	<p><b>DIMENSIONS:</b></p>	<p><b>PCB-LAYOUT:</b></p>
------------------------	--------------------------------------	------------------------------	---------------------------	---------------------------

The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	9
Contact type	sockets
Contact diameter	3_03_6_07mm
Insulator material	peek
Termination	pcb
Termination diameter	03mm08mm
Data transmission	usb_2_power

reverse\_gender\_on\_request

Connection diagram

con\_usb\_2\_power

Technical information

Nominal current single contact	1_5_a	iec_60512_5_2
Test voltage	075_kv_dc	eia_364_20f

safety\_text

## Mechanical and environmental data

Degree of protection*	ipsk8_ip6k9k
-----------------------	--------------

Operating temperature	51_125_c
-----------------------	----------

Mating cycles	5000
---------------	------

mated

## Material and surface treatments

Housing	ruthenium
---------	-----------

Contact	cu_alloy_gold
---------	---------------

safety\_text\_2

data\_text

ul\_text

illustrative\_text