

General information

Part number	GKOWDM-P12UM00-000L
Termination	pcb
Size	0
Locking principle	break
Coding	d_key_amc
Cable Diameter	cable_amchd_0



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.

<p>CODING:D</p>	<p>POSITIONS: 12 positions</p>	<p>PANEL CUT OUT:</p>	<p>DIMENSIONS:</p>	<p>PCB-LAYOUT:</p>
------------------------	---------------------------------------	------------------------------	---------------------------	---------------------------

The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	12
Contact type	sockets
Contact diameter	10_03_2_07mm
Insulator material	peek
Termination	pcb
Termination diameter	03mm08mm
Data transmission	usb_32

reverse_gender_on_request

Connection diagram

con_usb_32

Technical information

Nominal current single contact	1_5_a	iec_60512_5_2
Test voltage	075_kv_dc	eia_364_20f

safety_text

Mechanical and environmental data

Degree of protection*	ipsk8_ip6k9k
-----------------------	--------------

Operating temperature	51_125_c
-----------------------	----------

Mating cycles	5000
---------------	------

mated

Material and surface treatments

Housing	ruthenium
---------	-----------

Contact	cu_alloy_gold
---------	---------------

safety_text_2

data_text

ul_text

illustrative_text