

General information

| | |
|-------------------|---------------------|
| Part number | GK1WCM-P27WBCO-000L |
| Termination | solder |
| Size | 1 |
| Locking principle | break |
| Coding | c_key_amc |
| Cable Diameter | cable_amchd_1 |



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.

CODING:C

POSITIONS: 27 positions

PANEL CUT OUT:

DIMENSIONS:

The pin layout corresponds to the view on the termination area

Contact insert description

| | |
|--------------------|---------|
| Number of contacts | 27 |
| Contact type | sockets |
| Contact diameter | 03mm |
| Insulator material | peek |
| Wire cross section | 28_awg |
| Termination | solder |
| Data transmission | hdmi_13 |

reverse_gender_on_request

Technical information

| | | |
|--------------------------------|-----------|---------------|
| Nominal current single contact | 01_a | iec_60512_5_2 |
| Test voltage | 075_kv_dc | eia_364_20f |

safety_text

Mechanical and environmental data

| | |
|-----------------------|--------------|
| Degree of protection* | ipsk8_ip6k9k |
| Operating temperature | 51_125_c |
| Mating cycles | 5000 |

mated

Material and surface treatments

| | |
|----------------|---------------|
| Housing | ruthenium |
| Contact | cu_alloy_gold |

safety_text_2
data_text
ul_text
illustrative_text