

General information

| | |
|-------------------|---------------------|
| Part number | GL2LOC-P04MPN0-0000 |
| Termination | solder |
| Size | 2 |
| Locking principle | break , push |
| Coding | 0_key |



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.

| | | | |
|--------------------------|--------------------------------------|------------------------------|---------------------------|
| <p>CODING: 0°</p> | <p>POSITIONS: 4 Positions</p> | <p>PANEL CUT OUT:</p> | <p>DIMENSIONS:</p> |
|--------------------------|--------------------------------------|------------------------------|---------------------------|

The pin layout corresponds to the view on the termination area

Contact insert description

| | |
|----------------------|--------------|
| Number of contacts | 4 |
| Contact type | pins |
| Contact diameter | 13mm |
| Insulator material | peek |
| Wire cross section | 18_awg |
| Termination | solder |
| Termination diameter | 14mm |
| Data transmission | ethernet_100 |

reverse_gender_on_request

Technical information

| | | |
|--|----------|---------------|
| Max. creepage and air clearance distance | 15_mm | 13_mm |
| Nominal current single contact | 15_a | iec_60512_5_2 |
| Nominal current insert | 15 A | vde_0298_4 |
| Test voltage | 18_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| | |
|-----------------------|----------|
| Degree of protection* | ip68 |
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

unmated

Material and surface treatments

| | |
|---------|---------------|
| Housing | m_chrome |
| Contact | cu_alloy_gold |

safety_text_2
data_text
ul_text
illustrative_text