


GXBMFG-P04LTS0-0001
medi_snap, type_gd



General information

Part number	GXBMFG-P04LTS0-0001
Termination	solder
Size	3,5
Locking principle	push
Coding	f_key_medi



Illustrations may differ from original product.
 Dimensions, unless otherwise specified, in mm.

<p>CODING: 90°</p>	<p>POSITIONS: 4 Positions</p>	<p>PANEL CUT OUT:</p>	<p>DIMENSIONS:</p>
---------------------------	--------------------------------------	------------------------------	---------------------------

The pin layout corresponds to the view on the termination area

Contact insert description

Number of contacts	4
Contact type	sockets
Contact diameter	20mm
Insulator material	peek
Wire cross section	14_awg
Termination	solder
Termination diameter	24mm

Technical information

Max. creepage and air clearance distance	14 mm	iec_60601_2mopp_2moop
Nominal current single contact	24_a	iec_60512_5_2
Nominal current insert	24 A	vde_0298_4
Test voltage	185_kv_ac	eia_364_20f

safety_text
 iec_60601_receptacle

Mechanical and environmental data

Degree of protection*	ip68
Operating temperature	50_120_c
Mating cycles	5000

mated_unmated

Insulator materials MEDI-SNAP®

pei_peek_size_b_o_a

Material and surface treatments

Housing	pei_gray
Color option	gray
Contact	cu_alloy_gold

safety_text_2
data_text
ul_text
illustrative_text