

K11M07-P09LCC0-6560
medi_snap, type_k1






General information

| | |
|--------------------------|---------------------|
| Part number | K11M07-P09LCC0-6560 |
| Termination | solder |
| Size | 1 |
| Locking principle | break , push |
| Coding | 0_key |
| Cable Diameter | cable_medi_65 |
| Cable outlet | standard |



Illustrations may differ from original product.
 Dimensions, unless otherwise specified, in mm.

| | | |
|--|--|---|
| <p>CODING: 0°</p>  | <p>POSITIONS: 9 Positions</p>  | <p>DIMENSIONS</p>  |
|--|--|---|

The pin layout corresponds to the view on the termination area

Contact insert description

| | |
|-----------------------------|---------|
| Number of contacts | 9 |
| Contact type | sockets |
| Contact diameter | 05mm |
| Insulator material | peek |
| Wire cross section | 28_awg |
| Termination | solder |
| Termination diameter | 045mm |

reverse_gender_on_request

Technical information

| | | |
|---|----------|-----------------------|
| Max. creepage and air clearance distance | 065_mm | iec_60601_1mopp_2moop |
| Nominal current single contact | 04_a | iec_60512_5_2 |
| Nominal current insert | 2,6 A | vde_0298_4 |
| Test voltage | 09_kv_ac | eia_364_20f |

safety_text

Mechanical and environmental data

| | |
|-----------------------|----------|
| Degree of protection* | ip50 |
| Operating temperature | 50_120_c |
| Mating cycles | 5000 |

mated_unmated

Insulator materials MEDI-SNAP®

psu_peek

Material and surface treatments

| | |
|--------------|---------------|
| Housing | psu_gray |
| Color option | blue |
| Contact | cu_alloy_gold |

safety_text_2
ul_text
illustrative_text