

## S1CLOC-P03MCCO-2000

odu\_mini\_snap®\_series\_l

### straight\_push\_pull\_plug

size: 00, IP50, keying: 0, number\_of\_contacts: 3, solder\_cup, contact\_type: pins, Signal



#### Basic information

|                    |                     |
|--------------------|---------------------|
| Part number        | S1CLOC-P03MCCO-2000 |
| Category           | connector           |
| Type of connector  | plug                |
| Assembly situation | straight            |
| Size               | 00                  |

#### Contact insert description

|                        |            |
|------------------------|------------|
| Transmission type      | Signal     |
| Number of contacts     | 3          |
| Contact type           | pins       |
| Contact diameter       | 0.5 mm     |
| Termination type       | solder_cup |
| Termination diameter   | 0.45 mm    |
| Wire cross section AWG | AWG 28     |

#### Technical information

|  |                             |  |
|--|-----------------------------|--|
| Max. current single contact                  | 4 A                         | IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003) |
| Max. current insert                          | 4                           | VDE 0298-4:2003                            |
| Test voltage                                 | 1.1 kV AC                   | SAE AS 13441:1998 method 3001.1            |
| Max. creepage distance (contact to contact)  | 0.5 mm (Contact to housing) |  |
| Max. creepage distance (contact to housing)  | 0.7 mm (Contact to housing) |  |
| Max. clearance distance (contact to contact) | 0.5 mm (Contact to contact) |  |
| Max. clearance distance (contact to housing) | 0.7 mm (Contact to housing) |  |

#### Cable description

|                     |          |
|---------------------|----------|
| Cable outlet        | back_nut |
| Min. cable diameter | 1.5      |
| Max. cable diameter | 2        |


## Mechanical and environmental data

|                            |           |
|----------------------------|-----------|
| Locking principle          | push_pull |
| Mating cycles              | 5.000     |
| IP class                   | IP50      |
| Max. operating temperature | 120 °C    |
| Min. operating temperature | -40 °C    |
| Weight                     | 3.62 g    |

## Material and surface treatments

|                  |                                  |
|------------------|----------------------------------|
| Material         | cu_alloy_with_matt_chrome_finish |
| Contact material | gold                             |


## DIMENSIONS



## CODING: 0 °



## POSITIONS: 3 Positions



### Further technical information and downloads

[3D-File \(STP File\)](#)

[Assembly Instruction](#)

[Technical specifications](#)