#### S1CLFC-P02MCC0-3500

# series\_I


# type\_s1



#### **General information**

Part number	S1CLFC-P02MCC0-3500	
Termination	solder	
Size	00	
Locking principle	push	
Coding	f_key	Illustrations may differ from original product. Dimensions, unless otherwise specified, in mm.
Cable Diameter	cable_mini_35	billiensions, unless otherwise specified, in filli.
Cable outlet	standard	





The pin layout corresponds to the view on the termination area

# **Contact insert description**

Number of contacts	2
Contact type	pins
Contact diameter	05mm
Insulator material	peek
Wire cross section	28_awg
Termination	solder
Termination diameter	045mm

reverse\_gender\_on\_request

#### **Technical information**

Max. creepage and air clearance distance	06_mm	08 <sub>_</sub> mm
Nominal current single contact	04_a	iec_60512_5_2
Nominal current insert	4 A	vde_0298_4
Test voltage	11_kv_ac	sae_13441

safety\_text

# Mechanical and environmental data

Degree of protection*	ip50
Operating temperature	40_120_c
Mating cycles	5000

mated\_unmated

### Material and surface treatments

Housing	m_chrome
Contact	cu_alloy_gold

safety\_text\_2 ul\_text illustrative\_text