S21KAC-P14MCC0-550S

series_k

type_s2

General information

| S21KAC-P14MCCO-550S | |
|---------------------|--|
| solder | |
| 1 | |
| push | |
| a_key | Illustrations may differ from origin Dimensions, unless otherwise spe |
| cable_mini_55 | Dimensions, uness otherwise spe |
| bend_relief | |
| | solder 1 push a_key cable_mini_55 |



The pin layout corresponds to the view on the termination area

Contact insert description

| Number of contacts | 14 |
|----------------------|--------|
| Contact type | pins |
| Contact diameter | 05mm |
| Insulator material | peek |
| Wire cross section | 28_awg |
| Termination | solder |
| Termination diameter | 045mm |
| | |

reverse_gender_on_request

Technical information

| Max. creepage and air clearance distance | 05_mm | 06_mm |
|--|----------|---------------|
| Nominal current single contact | 04_a | iec_60512_5_2 |
| Nominal current insert | 2 A | vde_0298_4 |
| Test voltage | 09_kv_ac | sae_13441 |

safety_text

ginal product. specified, in mm.

Mechanical and environmental data

| Degree of protection* | ip68 |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated

Material and surface treatments

| Housing | m_chrome |
|---------|---------------|
| Contact | cu_alloy_gold |

safety_text_2 ul_text illustrative_text