S21L0C-P03MPH0-720S

series I

type_s2




General information


| Part number | S21L0C-P03MPH0-720S | |
|-------------------|---------------------|------------------|
| Termination | solder | |
| Size | 1 | |
| Locking principle | push | |
| Coding | 0_key | Illustr Dimer |
| Cable Diameter | cable_mini_72 | Dilliel |
| Cable outlet | bend_relief | |



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.







The pin layout corresponds to the view on the termination area

Contact insert description

| Number of contacts | 3 |
|----------------------|--------|
| Contact type | pins |
| Contact diameter | 13mm |
| Insulator material | peek |
| Wire cross section | 20_awg |
| Termination | solder |
| Termination diameter | 11mm |

reverse_gender_on_request

Technical information

| Max. creepage and air clearance distance | 09_mm | 11_mm |
|--|----------|---------------|
| Nominal current single contact | 12_a | iec_60512_5_2 |
| Nominal current insert | 12 A | vde_0298_4 |
| Test voltage | 15_kv_ac | sae_13441 |

safety_text

Mechanical and environmental data

| Degree of protection* | ip50 |
|-----------------------|----------|
| Operating temperature | 40_120_c |
| Mating cycles | 5000 |

mated_unmated

Material and surface treatments

| Housing | m_chrome |
|---------|---------------|
| Contact | cu_alloy_gold |

safety_text_2 ul_text illustrative_text