### S21LAC-P04MJG0-720S

### series I

# type\_s2



#### **General information**


Part number	S21LAC-P04MJG0-720S	
Termination	solder	
Size	1	
Locking principle	push	
Coding	a_key	Illustr Dimer
Cable Diameter	cable_mini_72	Dilliel
Cable outlet	bend_relief	



Illustrations may differ from original product.
Dimensions, unless otherwise specified, in mm.







The pin layout corresponds to the view on the termination area

## Contact insert description

Number of contacts	4
Contact type	pins
Contact diameter	09mm
Insulator material	peek
Wire cross section	22_awg
Termination	solder
Termination diameter	085mm
Data transmission	ethernet_100

reverse gender on request

#### **Technical information**

Max. creepage and air clearance distance	10 <sub>_</sub> mm	14_mm
Nominal current single contact	075_a	iec_60512_5_2
Nominal current insert	7,5 A	vde_0298_4
Test voltage	15_kv_ac	sae_13441
safety_text		

# Mechanical and environmental data

Degree of protection*	ip50
Operating temperature	40_120_c
Mating cycles	5000

mated\_unmated

illustrative\_text

### Material and surface treatments

Housing	m_chrome	
Contact	cu_alloy_gold	
safety_text_2 data_text		
ul_text		