

**Basic information**

|                    |                     |
|--------------------|---------------------|
| Part number        | S30F1C-P04MFG0-2500 |
| Category           | connector           |
| Type of connector  | plug                |
| Assembly situation | straight            |

**Contact insert description**

|                        |            |
|------------------------|------------|
| Transmission type      | Signal     |
| Number of contacts     | 4          |
| Contact type           | pins       |
| Contact diameter       | 0.7 mm     |
| Termination type       | solder_cup |
| Termination diameter   | 0.85 mm    |
| Wire cross section AWG | AWG 22     |

**Technical information**

|                                              |                             |                                            |
|----------------------------------------------|-----------------------------|--------------------------------------------|
| Nominal current single contact               | 7.5 A                       | IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003) |
| Max. current insert                          | 7.5                         | VDE 0298-4:2003                            |
| Test voltage                                 | 0.9 kV AC                   | SAE AS 13441:1998 method 3001.1            |
| Max. creepage distance (contact to contact)  | 0.6 mm (Contact to housing) |                                            |
| Max. creepage distance (contact to housing)  | 0.7 mm (Contact to housing) |                                            |
| Max. clearance distance (contact to contact) | 0.6 mm (Contact to contact) |                                            |
| Max. clearance distance (contact to housing) | 0.7 mm (Contact to housing) |                                            |

**Cable description**

|                     |          |
|---------------------|----------|
| Cable outlet        | back_nut |
| Min. cable diameter | 2        |
| Max. cable diameter | 2.5      |

**Mechanical and environmental data**


|                            |           |
|----------------------------|-----------|
| Locking principle          | push_pull |
| Keying                     | 1         |
| Mating cycles              | 5000      |
| IP class                   | IP68      |
| Max. operating temperature | 120 °C    |
| Min. operating temperature | -40 °C    |

ip\_protection\_class\_refers\_to\_mated\_condition


**Material and surface treatments**

|                    |                                  |
|--------------------|----------------------------------|
| Material           | cu_alloy_with_matt_chrome_finish |
| Insulator material | peek                             |
| Contact material   | cu_alloy_with_gold_finish        |


## DIMENSIONS:



## CODING:1



## POSITIONS: 4 positions



## Further technical information and downloads

[3D-File \[STP File\]](#)

[Assembly Instruction](#)