



## Basic information

|                    |                     |
|--------------------|---------------------|
| Part number        | S41F1C-P06MFG0-350S |
| Category           | connector           |
| Type of connector  | plug                |
| Assembly situation | straight            |
| Size               | 1                   |

## Contact insert description

|                        |            |
|------------------------|------------|
| Transmission type      | Signal     |
| Number of contacts     | 6          |
| Contact type           | pins       |
| Contact diameter       | 0.7 mm     |
| Termination type       | solder_cup |
| Termination diameter   | 0.85 mm    |
| Wire cross section AWG | AWG 22     |

## Technical information

|                                              |                             |                                            |
|----------------------------------------------|-----------------------------|--------------------------------------------|
| Nominal current single contact               | 7.5 A                       | IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003) |
| Max. current insert                          | 5.625                       | VDE 0298-4:2003                            |
| Test voltage                                 | 1 kV AC                     | SAE AS 13441:1998 method 3001.1            |
| Max. creepage distance (contact to contact)  | 0.6 mm (Contact to housing) |                                            |
| Max. creepage distance (contact to housing)  | 0.8 mm (Contact to housing) |                                            |
| Max. clearance distance (contact to contact) | 0.6 mm (Contact to contact) |                                            |
| Max. clearance distance (contact to housing) | 0.8 mm (Contact to housing) |                                            |

## Cable description

|                     |                   |
|---------------------|-------------------|
| Cable outlet        | cable_bend_relief |
| Min. cable diameter | 3                 |
| Max. cable diameter | 3.5               |

**Mechanical and environmental data**


|                            |           |
|----------------------------|-----------|
| Locking principle          | push_pull |
| Keying                     | 1         |
| Mating cycles              | 5.000     |
| IP class                   | IP68      |
| Max. operating temperature | 120 °C    |
| Min. operating temperature | -40 °C    |
| Weight                     | 21.89 g   |

ip\_protection\_class\_refers\_to\_mated\_condition


**Material and surface treatments**

|                  |                                  |
|------------------|----------------------------------|
| Material         | cu_alloy_with_matt_chrome_finish |
| Contact material | cu_alloy_with_gold_finish        |


## DIMENSIONS:



## CODING:1



## POSITIONS: 6 positions



## Further technical information and downloads

[3D-File \[STP File\]](#)

[Assembly Instruction](#)