

straight_push_pull_plug_for_bend_relief

size: 1, IP64, keying: 0, number_of_contacts: 6, solder_cup, contact_type: pins, Signal



Basic information

| | |
|--------------------|---------------------|
| Part number | S41M07-P06MFD0-397S |
| Category | connector |
| Type of connector | plug |
| Assembly situation | straight |
| Size | 1 |

Contact insert description

| | |
|------------------------|-----------------------------|
| Special features | iec_60601_1_2_mopp_&_2_moop |
| Transmission type | Signal |
| Number of contacts | 6 |
| Contact type | pins |
| Contact diameter | 0.7 mm |
| Termination type | solder_cup |
| Termination diameter | 0.65 mm |
| Wire cross section AWG | AWG 26 |

Technical information

| | | |
|--|------------------------------|--|
| Nominal current single contact | 6 A | IEC 60512-5-2:2002 (DIN EN 60512-5-2:2003) |
| Max. current insert | 4.5 | VDE 0298-4:2003 |
| Test voltage | 1.1 kV AC | EIA-364-20F:2019-02 |
| Max. creepage distance (contact to contact) | 0.85 mm (Contact to housing) | |
| Max. creepage distance (contact to housing) | IEC 60601-1: 2MOPP, 2MOOP* | |
| Max. clearance distance (contact to contact) | 0.85 mm (Contact to contact) | |
| Max. clearance distance (contact to housing) | IEC 60601-1: 2MOPP, 2MOOP* | |

Cable description

| | |
|---------------------|-------------------|
| Cable outlet | cable_bend_relief |
| Min. cable diameter | 2.7 |
| Max. cable diameter | 3.9 |

Mechanical and environmental data

| | |
|----------------------------|-----------|
| Locking principle | push_pull |
| Mating cycles | 2000 |
| IP class | IP64 |
| Max. operating temperature | 120 °C |
| Min. operating temperature | 50 °C |

ip_protection_class_refers_to_mated_condition

Material and surface treatments

| | |
|----------------------------------|---------------------------|
| Material | psu_gray |
| Insulator material | peek |
| Contact material | cu_alloy_with_gold_finish |
| Color option (Front or back nut) | gray |

Insulator materials MEDI-SNAP®

psu_peek

DIMENSIONS:



CODING: 0°



POSITIONS: 6 Positions



Further technical information and downloads

[3D-File \[STP File\]](#)

[Assembly Instruction](#)